



PFK 筒夾刀把

PFK COLLET CHUCK



Balancing / 動平衡

G6.3

Max.25,000 RPM
Or U ≤ 1gmm

Option / 選配

G2.5

Max.25,000 RPM
Or U ≤ 1gmm

Dimensions / 尺寸標示

FIG.1A

FIG.2A

Order No. 訂購編號	FIG	Range 夾持範圍	ød	ød1	ød2	L	L1	L2	Tool Clamping Depth L3 刀具夾持 深度	page.147 page.144 page.117 page.148 			
										Nut 螺帽	Screw 調整螺絲	Collet 筒夾	Wrench 扳手
HSK50A	PFK6-100	1	1.75~6.0	19.5	32	100	74	63	21~35	CAP-PFK6	PFK-M8	SK6-P	PHS-PFK6
	PFK10-100	2	1.75~10.0	27.5	27.5	100	74	-	30~40	CAP-PFK10	PFK-M12	SK10-P	PHS-PFK10
	PFK16-100	2	2.75~16.0	40	40	100	74	-	40~48	CAP-PFK16	PFK-M12	SK16-P	PHS-PFK16
HSK63A	PFK6-100	1	1.75~6.0	19.5	32	100	74	63	21~35	CAP-PFK6	PFK-M8	SK6-P	PHS-PFK6
	PFK10-105	2	1.75~10.0	27.5	27.5	105	79	-	30~40	CAP-PFK10	PFK-M12	SK10-P	PHS-PFK10
	PFK16-105	2	2.75~16.0	40	40	105	79	-	40~48	CAP-PFK16	PFK-M12	SK16-P	PHS-PFK16
	PFK25-120	2	16.0~25.4	55	55	120	94	-	50~61	CAP-PFK25	PFK-M12	SK25-P	PHS-PFK25

Remarks / 備註

- 需配合 3µ P 筒夾 With 3µ P Grade Collet

Applications / 應用

