

CR 標準型熱縮刀把
CR STANDARD SHRINK FIT CHUCK



Balancing / 動平衡

G6.3
Max.30,000 RPM
Or U ≤ 1gmm

Option / 選配
G2.5
Max.30,000 RPM
Or U ≤ 1gmm

Dimensions / 尺寸標示

page.144

Order No. 訂購編號		ød	ød1	ød2	L	L1	L2	Tool Clamping Depth L3 刀具夾持深度	Screw 調整螺絲
HSK32E	CR04-060	4	14	19.9	60	40	20	min15	-
	CR06-070	6	21	26	70	50	28.6	25.5~31.5	HY06-M5
	CR08-070	8	21	26	70	50	28.6	30.5~35.5	HY08-M6
	CR10-080	10	24	26	80	60	38.2	36.5~41.5	HY08-M6
HSK40E	CR04-060	4	14	19.9	60	40	39.1	min15	-
	CR06-080	6	21	27	80	60	34.3	25.5~31.5	HY06-M5
	CR08-080	8	21	27	80	60	34.3	30.5~35.5	HY08-M6
	CR10-080	10	24	32	80	60	47	36.5~41.5	HY08-M6
HSK50E	CR04-080	4	14	21	80	54	40.7	min15	-
	CR06-080	6	21	27	80	54	34.3	25.5~31.5	HY06-M5
	CR08-080	8	21	27	80	54	34.3	30.5~35.5	HY08-M6
	CR10-085	10	24	32	85	59	47	36.5~41.5	HY08-M6
	CR12-090	12	24	32	90	64	47	41.5~46.5	HY14-M8
	CR16-095	16	27	34	95	69	40.7	44.5~49.5	HY18-M12

Remarks / 備註

- 刀具柄徑公差 h6(h6 Tooling Diameter Tolerance)
- 若需搭配中心出水管，請參考 page.145 規格表
- 若需出水型刀把，請參考 page.26 選用說明

Applications / 應用



Drilling
鑽孔



Reaming
銚孔



Endmilling
銑削