

# PFK 高速全圓螺帽刀把

## PFK HIGH SPEED COLLET CHUCK WITH ROUND NUT



HSK-E DIN 69893 FORM E

Balancing / 動平衡	Dimensions / 尺寸標示
<p><b>G6.3</b> Max.30,000 RPM Or U ≤ 1gmm</p> <p>Option / 選配 <b>G2.5</b> Max.30,000 RPM Or U ≤ 1gmm</p>	

page.147

page.144

page.117

page.149



Order No. 訂購編號	Range 夾持範圍	ød	ød1	L	L1	Tool Clamping Depth L2 刀具夾持深度	Nut 螺帽	Screw 調整螺絲	Collet 筒夾	Wrench 扳手
HSK40E	PFK10-080S	1.75~10.0	27.5	80	60	max58.5	CAP-PFK10S	-	SK10-P	PHS-10-TW275
	PFK16-080S	2.75~16.0	40	80	60	max49.5	CAP-PFK16S	-	SK16-P	PHS-20-RO400
HSK50E	PFK10-100S	1.75~10.0	27.5	100	74	30~40	CAP-PFK10S	PFK-M12	SK10-P	PHS-10-TW275
	PFK16-100S	2.75~16.0	40	100	74	40~48	CAP-PFK16S	PFK-M12	SK16-P	PHS-20-RO400

Remarks / 備註

- 需配合 3μ P 筒夾 With 3μ P Grade Collet

Applications / 應用



Drilling  
鑽孔



Reaming  
銜孔



Endmilling  
銑削



Tapping  
攻牙