

PFK 筒夾刀把

PFK COLLET CHUCK



Balancing / 動平衡	Dimensions / 尺寸標示
<p>G6.3</p> <p>Max.30,000 RPM Or $U \leq 1\text{gmm}$</p> <p>Option / 選配</p> <p>G2.5</p> <p>Max.30,000 RPM Or $U \leq 1\text{gmm}$</p>	

HSK-E DIN 69893 FORM E

Order No. 訂購編號	FIG	Range 夾持範圍	Range ϕd			Tool Clamping Depth L3							
			$\phi d1$	$\phi d2$	L	L1	L2	刀夾持深度	Nut 螺帽	Screw 調整螺絲	Collet 筒夾	Wrench 扳手	
HSK40E	PFK6-080	2	1.75~6.0	19.5	19.5	80	-	60	21~30	CAP-PFK6	PFK-M8	SK6-P	PHS-PFK6
	PFK10-080	2	1.75~10.0	27.5	27.5	80	-	60	max58.5	CAP-PFK10	-	SK10-P	PHS-PFK10
	PFK16-080	2	2.75~16.0	40	40	80	-	60	max49.5	CAP-PFK16	-	SK16-P	PHS-PFK16
HSK50E	PFK6-100	1	1.75~6.0	19.5	32	100	63	74	21~35	CAP-PFK6	PFK-M8	SK6-P	PHS-PFK6
	PFK10-100	2	1.75~10.0	27.5	27.5	100	-	74	30~40	CAP-PFK10	PFK-M12	SK10-P	PHS-PFK10
	PFK16-100	2	2.75~16.0	40	40	100	-	74	40~48	CAP-PFK16	PFK-M12	SK16-P	PHS-PFK16

Remarks / 備註

- 需配合 3 μ P 筒夾 With 3 μ P Grade Collet

Applications / 應用

