

SR 細長型熱縮刀把

SLIM TYPE SHRINK FIT CHUCK



Balancing / 動平衡

G6.3
Max.25,000 RPM
Or U ≤ 1gmm

Option / 選配
G2.5
Max.25,000 RPM
Or U ≤ 1gmm

Dimensions / 尺寸標示

page.144

Order No. 訂購編號		ød	ød1	ød2	L	L1	L2	L3	Tool Clamping Depth L4 刀具夾持深度	Screw 調整螺絲
HSK50A	SR04-125	4	10	19.7	125	99	96.2	20	min15	-
	SR06-125	6	12	21.7	125	99	96.2	25	25.5~31.5	HY06-M5
	SR08-125	8	14	23.8	125	99	96.2	35	30.5~35.5	HY08-M6
	SR10-125	10	16	25.8	125	99	96.2	40	36.5~41.5	HY08-M6
HSK63A	SR04-120	4	10	19	120	94	89.3	20	min15	-
	SR04-150	4	10	22.1	150	124	119.3	20	min15	-
	SR06-120	6	12	21	120	94	89.3	25	25.5~31.5	HY06-M5
	SR06-150	6	12	24.1	150	124	119.3	25	25.5~31.5	HY06-M5
	SR08-120	8	14	23.1	120	94	89.3	35	30.5~35.5	HY08-M6
	SR08-150	8	14	26.1	150	124	119.3	35	30.5~35.5	HY08-M6
	SR10-120	10	16	25.1	120	94	89.3	40	36.5~41.5	HY08-M6
	SR10-150	10	16	28.1	150	124	119.3	40	36.5~41.5	HY08-M6
	SR12-120	12	18	27.1	120	94	89.3	45	41.5~46.5	HY14-M8
HSK100A	SR04-165	4	10	22.3	165	136	121.8	20	min15	-
	SR06-165	6	12	24.3	165	136	121.8	25	25.5~31.5	HY06-M5
	SR08-165	8	14	26.4	165	136	121.8	35	30.5~35.5	HY08-M6
	SR10-165	10	16	28.4	165	136	121.8	40	36.5~41.5	HY08-M6
	SR12-165	12	18	30.4	165	136	121.8	45	41.5~46.5	HY14-M8

Remarks / 備註

- 直接夾持精度 Direct Clamping
- 刀具柄徑公差 h6(h6 Tooling Diameter Tolerance)

Applications / 應用

Drilling
鑽孔

Reaming
鉋孔

Endmilling
銑削

Mini Diameter
小徑加工